


# POST SHORE - B Series HEAVY DUTY - EXPOSED THREAD

PUNTALES DE METAL AJUSTABLES - Serie B SERVICIO PESADO - ROSCA EXPUESTA

Adjustment with pin and levered handle



**Heavy duty model Post Shore with exposed thread, cast collar with single lever type handle, end plates 4.75" x 4.75" x .32" (140mm x 140mm x 8mm), painted green.**

**Optional: Reinforced base, pin on cable.**

*Modelo de puntal de servicio pesado con roscas expuestas, cuello colado con una sola agarradera tipo palanca, placas extremo 140mm x 140mm x 8mm (4.75" x 4.75" x .32"), pintado de verde.*

*Opcional: Base reforzada, sujetador en cable.*

# ABLE

**EXPORT, LLC**  
7475 NW 63rd Street  
Miami, FL 33166-3603  
Miami: (305) 593-2253  
Fax: (305) 592-2793  
USA WATS: 1-800-831-4564

**AMERICAN SYSTEM**  
SISTEMA E.U.A.

**METRIC SYSTEM**  
SISTEMA MÉTRICO



	Length/Longitud:	External tube/Tubo externo:	Internal tube/Tubo interno:	Weight/Peso:
<b>PS-1B</b> 1,000/20' CONT. Special Order	5'9" to/a 10'3"	2.36" x .146" x 5'5"	1.89" x .150" x 5'7"	38 lbs./libras
<b>PS-2B</b> 800/20' CONT.	6'6" to/a 11'0"	2.36" x .146" x 5'5"	1.89" x .150" x 6'5"	41.7 lbs./libras
<b>PS-3B</b> 800/20' CONT.	8'6" to/a 13'0"	2.36" x .146" x 6'8"	1.89" x .150" x 7'2"	45.6 lbs./libras
<b>PS-4B</b> 450/20' CONT.	10'6" to/a 16'0"	2.36" x .146" x 6'7"	1.89" x .150" x 10'5"	56.1 lbs./libras

### ALLOWABLE LOADS IN LBS:

CARGAS PERMISIBLES EN KGS:

**SAFETY FACTOR = 3:1 FACTOR DE SEGURIDAD = 3:1**

HEIGHT / ALTURA	5'	6'	7'	8'	9'	10'	11'	12'	13'	14'	15'
	1.52m	1.83m	2.13m	2.44m	2.74m	3.05m	3.35m	3.66m	3.96m	4.27m	4.57m
<b>PS-1B</b>	10,600 4,808	9,800 4,445	8,800 3,992	7,800 3,538	6,800 3,084						
<b>PS-2B</b>			7,300 3,311	7,150 3,243	7,000 3,175	5,600 2,540	4,200 1,905				
<b>PS-3B</b>					6,500 2,948	6,200 2,812	5,950 2,698	4,600 2,086	3,350 1,519		
<b>PS-4B</b>						7,000 3,175	6,450 2,925	5,900 2,676	4,500 2,041	3,600 1,632	2,500 1,133